

Size		M14	M16	M18	M20	M22	M24	M26	M30	M36	M42	M45	M52
Working Pressure (Stell)	MPa	50	50	50	50	50	50	50	40	40	40	40	40
	psi	7251	7251	7251	7251	7251	7251	7251	5802	5802	5802	5802	5802
Working Pressure (Aluminum)	MPa	40	40	40	40	40	40	40	30	30	30	30	30
	psi	5802	5802	5802	5802	5802	5802	5802	4351	4351	4351	4351	4351
Burs Pressure (Stell)	MPa	100	100	100	100	100	100	100	95	95	85	85	85
	psi	14500	14500	14500	14500	14500	14500	14500	13779	13779	12328	12328	12328
Burst Pressure (Aluminum)	MPa	80	80	80	80	80	80	80	75	75	65	65	65
	psi	11603	11603	11603	11603	11603	11603	11603	10878	10878	9427	9427	9427
Max.Fulow Suggasted	l/min	42	56	70	70	185	185	185	274	364	592	592	592
	GPM	11	15	18.5	18.5	49.0	49.0	49.0	73	96	156.5	156.5	156.5
Weight (Aliminum)	kğ	0.27	0.28	0.29	0.30	0.40	0.40	0.40	0.89	0.92	1.28	1.28	1.57
	lbs	0.59	0.62	0.64	0.66	0.88	0.88	0.88	1.96	2.03	2.82	2.82	3.46
Weight (Stell)	kğ	0.41	0.42	0.43	0.44	0.62	0.62	0.62	1.31	1.34	1.96	1.96	2.25
	lbs	0.90	0.93	0.95	0.97	1.37	1.37	1.37	2.89	2.95	4.32	4.32	4.96

Fluid:OIL ISO VG46
Temperature:40°C
Viscosity:41.4-50.6 mm²/s
Test Pressure:5 Bar
Test in Accordance:ISO 18869:2017

Temperature Range:
Seals in NBR (Nitrile): From -20°C to +100°C (-4°F to +121°F)